BODY :	TB34DA PUMPER	STYLE 75'	Aerial/500	lb.	OAH
PART NO	DESCRIPTI	ON	(YTY	
00-00-00	BODY ======== BODY == Master list Update Warranty	===== BOD	Y) Revised	1	
	Standard one year 10	0% parts &	labor.		
00-00-41 00-00-42 00-00-43 00-02-04 00-02-05 00-02-10 00-02-15 00-02-20 00-02-25 S<	10 Year Structural Ca 10 Year Corrosion Per 20 Year Aerial Struct Intent of Specificati Quality and Workmansh Performance Test and Failure To Meet Test Liability Delivery/Training	foration W ural Warra ons (75' P ip	arranty nty Body) ts	1	
00-02-42 S 00-02-45 S 00-02-51 10-00-51 S 10-10-01 S 10-11-01	A minimum of 16 hour training shall be princludes a Campbell representative and a representative. Maintenance Manuals Parts Manuals General Construction Exception To Specificated Bond - 10% Performance Bond - 10% Approval Drawings Tilt Pumper W/75' Aer: Frame - 10.25" Wide Bumper - 10" (Tilt & 22" Bumper Extension The extension can be 6".	ovided. The Supply Seagrave ations ations ations "J" Cab One No Hose	Eactory WB Singl		
10-22-02 S 10-25-01 10-28-01 S 10-30-02	Modification for Rec A Painted Front Tow Hook Painted Rear Tow Loops Ross TAS-85 Steering Air Piping/System - Tv Spicer 1810 Driveline R/S FL-943 Axle S-Cam	cs s (Tilt) vo Axles		1 1 1 1 1 1 1 1	

Quote No : 00000-001 Job No: MONTVILLE

03/18/98		Page 2
PART NO DESCRIPTION	QTY	
Axle capacity is 21,500 lbs		
11-00-90 Aux. Air Applied Frt Axle Park Brake (Aer 11-10-12 < RS-30-180 W/16-1/2"x7" S-Cam Brakes 31		
Axle capacity is 31,000 lbs		
11-20-26 S Anti-Lock Braking System - Single Axle 11-20-29 < Automatic Traction Control (ATC)	1	
This interfaces with with the ABS system.		
11-30-01 S Standard Suspension - Tilt Cab Pumper 12-05-62 S< GY/425/65E22 5/J/G286/Frt/Hwy 11,230 lb.	. 2	
Michelin tires are available.		
12-06-09 S< GY/315/80R22.5/J/G124/Rear/Agr 8,140 lb.	. 4	
These tires are Mud & Snow tread.		
12-90-01 < STD Steel Disc Wheels	1	
Aluminum wheels or Real Wheels polished stainless steel wheel covers/inserts are available.		V 10-00-0-05 g
13-00-26 < Detroit Series 60 430 HP (12.7L) DDEC II	1	
Cummins engines are also available.		
13-00-70 EPQ Certification 13-01-21 Silicone Hoses 13-03-15 S Allison HD-4060P Electronic Transmission 13-08-01 S 50 Gallon Fuel Tank 13-10-14 Alternator - Niehoff 290 AMP Model A1-60 13-12-02 B/W TU-FLO 750 16.5 CFM Air Compressor 13-12-01 Farr Ecolite Air Cleaner (Tilt) 13-12-51 Air Restriction Indicator STD 13-13-01 Std Horizontal Exhaust RH Side 13-15-02 < Jacobs Engine Brake - 6 Cylinder (Ser. 6)	1 1 1 1 1	
Various retarders are available - transmiss on retarder; Telma driveline retarder.		
13-15-21 Fast Idle Switch 20-00-01 S< 6 Person Galvanneal Steel Full Tilt Cab	1	
The cab is also offered in stainless steel.		
20-25-01 Engine Hood (Tilt) 20-25-55 S Pre-plan Book/Map Box On Engine Hood 20-26-01 < Radio Compartment (STD Tilt)	1 1	
Compartment is located under the	145) 25 120	

03/18/98			Page
PART NO	DESCRIPTION	QTY	~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~
	officer's seat.	~~~~~~~~~	
20-26-10	< 1 1/4" Radio Conduit Radio Comp't To Das	1	
	Provides a conduit from the radio compartment located under the officer's seat to the cab dash.		
20-26-15	< Buss Bar Por Radio Compartment	1	
	Provides easy access to wiring hook-up for the radio installer.		
20-30-02 20-50-02	Polished Stainless Steel Front Fenders < Powered Rcof Exhaust Fans-2	1	
	Should air conditioning be chosen, these fans shall be deleted.		2
20-50-13 21-00-25	< Bostrom Sierra Fixed Driver's Seat (STD	1	
	Seat is a mid back, mechanically adjustable seat. Other seats are available.		at Sh Fyel a
21-00-50	< Bostrom Sierra Fixed Officer's Seat (STD	1	
	Same seat as above. SCBA style seats are available.	1	
21-10-51	< Fold Down Jump Seats in Cab (2)	1	
	These are non-SCBA type and are located on the back wall of the cab.		
21-11-03	< T6-3 Rear Seating Option	1	, N
20 as	This option provides four (4) rear facing Bostrom SCBA seats. Additional options, including forward facing SCBA seats are available.	v 2. 0 s****	
21-13-01 21-13-02 21-13-10	Std Retract Seat Belts W/Frt Shoulder Ha 3-Pt. Shoulder Harness (Per seat) < Black Viny: Interior Upholstery	1 2 1	
	Other upholstery colors are available.		
21-13-25 21-20-01 21-20-20	Capacity Sign (STD) Windshield (Tinted) < Door Glass (Tinted)	1 1 1	
	Power windows are available.		
21-22-10 21-22-12 21-22-51 21-23-01 21-23-27		1 1 1 1	

03/18/98			Page	4
PART NO		QTY		
21-25-02 21-26-01	Tilt Steering Wheel Telescoping < Std Cab Mounted Handrails & Grab Handles	1		
	Includes an 18" grab rail at each cab door and a chrome plated grab rail on the inside of each cab door.			
21-26-11	< 8" Grab Handle (Rubber Covered) each	4		
	These are included as extra.			
21-27-01	< Mirrors 6x16 West Coast W/Convex (Alum)	1		
	Other style mirrors, including "bus" style and remote controlled heated mirrors are available.			
21-28-01 21-28-02 21-28-03 21-50-30 22-00-01 22-00-13 22-01-02 22-01-07 22-01-16 22-10-03	Vehicle Height Sign Cab Dash and Instruments (Tilt W/Pump) Std. VDO Gauges Stewart Warner Electronic Speedometer	1		
	Batteries are Group 31 deep cycle style			
22-15-21 22-15-38 S 22-15-55		1 1 1 1 1		
	All wiring is function & color coded every 4".			
22-20-03 23-00-01 23-00-03 23-00-11 23-01-01 23-02-05 23-02-90 23-03-01 23-10-02 23-10-12	Whelen 64 Geries Front Directional Light Side Mounted "Bug Eye" Directionals STD	1 1 1 1 1 1 1 1		
	Included for each folding step located on the apparatus.			
23-10-14 S 23-11-01 23-11-24 S	Interior Lights (Std)	1 1 3		

03/18/98			Page
PART NO		QTY	
23-11-26 23-25-01	Automatic Door Switches for Do < Std Compartment Lights	me Lights 1 1	
	Includes a 5" diameter light ceiling of each compartment.	in the	
23-25-06 24-00-01	STD 7" Hazard Warning Light in code 3 XL9100-22" Lightbar ((7.8 Amps) 1	
	Many options are available for warning light systems.	or the	
	These 22" lights shall be loc the cab roof, one each side.	ated on	
24-00-65	< Code 3 OL13F Hdlgt Mnt Oscila	ser (2.5 A 2	
	To be located on the front of in a headlight style housing.	the cab,	Wide .
24-00-84	< Code 3 Model 4135BZ Wn. Light	(Halg) 2.7 8	
	Lights are to be located (3) (2) in the rear.	each side;	. Jak
24-00-97	< Code 3 Model 550F Rotating Bea		
	To be located (1) each side i upper portion.	n the rear	
24-02-61	< Whelen 64 L/Levl Warn. Light	(Halg.)(2 2	
	To be located on the front of inboard of the oscillaser lig	the cab,	
24-03-00 24-90-01		091-75) 3	
	The load manager has an autom hi-idle feature and shall act when the parking brake is set	ivate only	
26-00-01 26-00-16 26-01-05 26-10-11 26-11-03 27-00-34	S Federal Mdl. BP100 Siren Spkr.	o DBA Adju 1 ectronic S 1 In Bumper 1	
	Various generator options & configurations are available.	•	
27-01-01	<pre></pre>	1	
27-01-03		Dash (Diese 1	
	This feature allows you to st stop the diesel generator fro		

03/18/98			Page 6
PART NO	DESCRIPTION	QTY	
27-05-03 27-05-31 S 27-05-42 <	Load Center - Up to Twelve Circuits Hannay Electric Cord Reel 10/3 Cable for Cord Reel (per 50 foot le A total of 200' is included for the	1 1 4	
	cord reel.		
27-05-52 <	Extenda-late 4-Outlet Junct. Box 20amp This junction box is for the cord on the reel It allows up to four appliances to be plugged in and run off of the generator.	1	
27-15-23 27-40-03 <	Kwik Raise 750 W Alpha 2000 Floodlight W Additional Remote Switches AC or 12V (ea	2 2	
	These switches are located on the cab dash and allow for the operator to activate the quartz light(s) from the cab.		
30-00-01 <	Operators Stand 60.5" Side Control - Gal		The state of the s
	This is the pump panel area and measures 60.5" wide. It features flex joints between the cab and the body.	n enwormen en ne ha a rai	
30-03-01 <	Master Pressure & Compound Gauges - 4 1/	1	
	6" diameter Master guages are available		
30-04-01 <	2-1/2" Span/Seagrave Pressure Gauge (Eac	6	
	3 1/2" diameter guages are available along with various flow meters.		
30-20-31 \$, 30-20-55	Fuel Gauge Voltmeter 'Pump Panel) "MC" Products Pump Overheat Indicator Stainless Steel Lt Shield for R/Side Pum Runningboards 3/16" Aluminum Diamond Pla Pull Out Step Under Runningboard Gripstrut Inserts For Pull Out Step Crosslay Hosebed (2) 1 1/2" W/2" Piping	1 1 1 1 1 1 1	
	The standard crosslay hosebed capacity is 200' of 1 3/4" double jacket hose.	k. **	
30-30-81 31-00-13 S<	Hinged Alum Dia. Cover for X-Lay W/Hold Waterous Pump 1250 GPM - 2 Stage Mdl. CM	1 1	
	Seagrave offers both Waterous and Hale pumps This pump is our standard base pump.		
31-01-60 <	Pump Packing Glands STD	1	

03/18/98		***		Page 7
PART NO		DESCRIPTION	QTY	
		Mechanical seals are available.		
31-01-71 31-02-02 31-03-01		Pump Lubrication Fitting on Panel Waterous Air Pump Shift w/Manual Overrid Waterous pressure Control Relief Valve	1 1	
		Electronic pressure governors are available		
31-04-01	<	Waterous Transfer Valve Manual Shift	1	
		Electric and air operated transfer valves are available.		
31-05-01	<	Waterous Priming Device Rotary Vane VPE	1	
		Rotary gear primers are avialable.		
32-00-01 32-01-01		Auxiliary Cooling System Pump Piping	1	" ## =
		Pump piping is galvanized steel piping. High pressure reinforced hose is utilized in some areas.	#Imat -	
32-02-05	<	utilized in some areas. 3/4" Quarter Turn Drain Valves IPOS (EA)	7	
		Drain valves are Class 1 and are included for all discharges & intakes.	wa a-	
32-02-06 33-00-01 33-00-11			2 1 1	*
8.77		Various intake piping sizes are available		
33-00-12 33-11-01 33-11-23 34-00-00 34-00-01	<	2-1/2" Right Side Hydrant Inlets Galv Pi 3" Tank to Pump Line (Side Panel Contro 1-1/2" Galvanized Tank Fill Main Discharge Verbiage 2-1/2" Left Side Disch Galv Piping Each	1 1 1 2	
	1	Various size discharges are available.		
34-00-02 34-04-01		2-1/2" Right Side Disch Galv Piping Each Push-Pull Controls	2 1	
		Akron style control handles are utilized.		
37-05-01	<	500 Gal T-Type Tank UPF Poly II Pumper W	1	
		Tank is a United Plastic Fabricators poly tank		
37-50-01 37-50-02 37-50-22 37-60-01		Booster Tank Clean Out Plug STD Tank Overflow Behind Rr Axle(Aerials onl "MC" Mark 5 Liquid Level Monitor w/Stain Hose Body W/Alum Slats	1 1 1	
		x Secretary		

03/18/98			Page
PART NO	DESCRIPTION	QTY	
37-61-01	< Hosebed Partitions Galvanneal	(Each) 1	
	Need to have hose load requir	ements.	
40-00-01 S	Pumper Body - Galvanneal Const	ruction 1	
	Stainless steel is offered as option.	an	
41-34-10	P/75 Standard Compartment L.H.	Side 1	
	This compartmentation is for l compts. with lift-up doors. Re doors are available.		
41-44-11	P/75 Option 1 Compartment R.H.	Side 1	
	This compartmentation is of the height style.	he 3/4	P.3.
41-50-91 41-90-00 41-91-01	False Bulkhead Inside Rear Comp Compartment Doors - Galvanneal Standard Interior Compartment I	1	
	Louvers are stamped into the abody sheetmetal.		
41-95-05 41-95-31 59-00-01 S 59-00-03	Turntable Access Ladders 75' "I	P" Body 1 ent & Shel 13	
	This is for one compartment ar the back wall to mount bracket	nd is for s into.	
59-00-21 <	Mike Compartment	1	
	Radio compartment is located a pump panel.	t the	
59-05-02 59-05-21	Polished Stainless steel Fender Mud Flaps Rear Axle		
	Wheel Well Air Bottle Compartme	nts (4) 1	
	Located (2) each side.		
59-07-23 59-10-01 <	Std. 26" Rear Step (1/8" Alum. Chrome Placed Folding Steps IAT	Dia. Pl.) 1 S (Ea) 4	
	Four (4) are provided as extra	s.	
59-15-01 S 59-15-10 S 59-20-03 60-00-01 60-00-50 S 60-05-02 60-10-02 60-20-01 S 60-30-01 S	Adjustable Shelves - Galvanneal Roll-out Tray 200 lb. Cap. Galv Stn Stl Scuff Strip Low Edge Hi Aerial Hydraulics System (75'& Hydraulic Oil Tank Shut-off Val Power Take/Off, Hydraulic Pump, Emergency Pump P/75 Hoist System - 75' Aerial Rotation System - 75' Aerial	anneal 1 Side Com 2 100') 1 Ve 1 Quint 1	
	Mariat	1	

03/18/98			Page	9
PART NO	DESCRIPTION	QTY	 	
60-35-01 60-40-01	Rotation Interlock System (All Aerials) Extension Retraction System (75') Hydraulic Swivel (All) Outriggers 75' Aerial	1 1 1 1		*
	Outriggers are of the out and down style and provide a 17' shoe to shoe stance. They also can be shortjacked for use on narrow roads.			
60-70-01 S 60-75-01 S 61-00-01 S		1 1 1 1 1 1 1 1 1		
	Ladder is of "K" braced, steel construction and is fabricated and assembled at the Seagrave factory.			
61-15-01 61-20-02 S	Folding Steps Tip of Ladder	1 1 1 1	ਤੰਬ ਨ ਵੱਧਨ	
	Located at the pump panel. Optional controls are available at the rear.	, a		
61-60-01 61-63-01 S	Aerial Intercom (75' "P" Body) Aktinson AD-26 Intercom Load Alarm	1 1 1 1 1 1 1 1 1 1		
1	waterway is capable of 1,000 GPM. The rear inlet can be utilized as an LDH discharge as well.	*** ** ** **		
61-70-21 <	Pinnable Waterway Feature (ALL AERIALS)			
	This feature allows the waterway nozzle to be located at either the tip of the fly section or the second section of the aerial.			
61-70-51 <	Remote Control Water Nozzle	1		
	Nozzle is controlled from the aerial ladder or the pump panel.			
61-75-26 S	6' Pike Pole Mounted On Fly Section 6 lb. Axe Mounted On Fly Section Aerial Capacities	1		

03/18/98	Page 10
PART NO DESCRIPTION QT	Y
Ladder capacity is 500 lbs. @ zero degrees and full extension, flowing 1,000 GPM.	
61-95-01 < Inspection Certificate	1
All Seagrave aerials are Underwriters Labratories third party tested at our facility.	
90-00-01 S< Duo Safety 900A 24'-2 and 775A 14' Ladde	1
NOTE - The ground ladder compliment on this style 75' allows for only a pumper compliment of ground ladders, mounted on the curbside.	
90-00-90 Standard Ladder Mounting 90-00-91 Leather Lined Ladder Brackets 90-00-93 Pull/Twis: Type Ladder Clamps STD 90-05-01 Std. Pike Poles 90-05-22 6' Pike Pole w/Fiberglass Handle 90-05-24 10' Pike Pole w/Fiberglass Handle	1 1 1 1 1 1 2
Pike poles are mounted above the ground ladders.	
91-00-00 S Paint Prep and Finish - Pumpers	1 1 1
Dupont Imron 5000 Series paint system is utilized 6000 Series is offered as an option.	
07 00 40 50	1
The undercarraige can be finish painted in a variety of finishes.	
	1
Options offered are painted finish to match truck color; oscillated finish, (stainless only); grey type spatter finish standard.	
91-00-80 Outriggers Painted Silver Blue Metallic 91-00-85 Torque Box & Ladder Stakes Finish (Std) 91-00-90 Paint Aerial Ladder White Polyurethane	
Upper 4' of the fly section of the aerial would be painted fluorescent	±1 di

03/18/98 Page QTY DESCRIPTION PART NO

Red.

91-03-04 S< 4" Reflective Striping - DFI

1

A minimum 4" wide reflective stripe is required by NFPA. Additional gold leafing or reflective letters/numbers are offered by Campbell Supply.