

9469355

PEF,12,F1,CI,NBR,CR*GS-12A-HD12

Style: PEF - 100% Area Rectangular Port Eccentric Plug Valve (AWWA C517) (PEF)

Size: 12 - 12 Inch (300mm); SST Bearings; Welded-in Nickel Seat

End Connection: F1 - Flanged Drilling; ASME Class 125/150

Body Material: CI - Cast Iron

Packing: NBR - Acrylonitrile-Butadiene; Temperature to 250° F.

Plug Facing: CR - Chloroprene; -20 to 180° F. (-29 to 83° C.)

Coating: SB0 - Exterior: 4 mils minimum of Blue Epoxy DeZURIK with Standard (SP10) surface prep

Actuator: GS-12A-HD12 - G-Series Handwheel; 12 In Dia

Weight (Approx): 488 lbs/ 222 kgs

Min Valve Temperature: -20 Degrees F.

Max Temperature: 180 Degrees F.

Max Valve Pressure: 175 psig

9492873

PEF,12,F1,CI,NBR,CR*GS-6A-N

Style: PEF - 100% Area Rectangular Port Eccentric Plug Valve (AWWA C517) (PEF)

Size: 12 - 12 Inch (300mm); SST Bearings; Welded-in Nickel Seat

End Connection: F1 - Flanged Drilling; ASME Class 125/150

Body Material: CI - Cast Iron

Packing: NBR - Acrylonitrile-Butadiene; Temperature to 250° F.

Plug Facing: CR - Chloroprene; -20 to 180° F. (-29 to 83° C.)

Coating: SB0 - Exterior: 4 mils minimum of Blue Epoxy DeZURIK with Standard (SP10) surface prep

Actuator: GS-6A-N - G-Series Nut; 2 In Square

Weight (Approx): 407 lbs/ 185 kgs

Min Valve Temperature: -20 Degrees F.

Max Temperature: 180 Degrees F.

Max Valve Pressure: 175 psig