Hydraulic Shears – SH-70250-HD / SH-120250-HD

SPECIFICATIONS – SH-70250-HD		
Shear Length	96"	2500 mm
Max. Material Thickness		
Mild Steel	.250"	6.3 mm
Stainless Steel	.177"	4.5 mm
Minimum Thickness	18 ga.	
Back Gauge Length	23.62"	600 mm
Blade Rake Angle	1.5°	
Blade Clearance	Manual Hand Wheel	
Motor	10 hp	
Power Requirements	220V 3-Phase	
Shipping Dimensions (L x W x H)	143" x 80" x 73"	3632 x 2032 x 1854 mm
Shipping Weight	10,525 lbs.	4785 kgs.

Specifications subject to change without notice.

- 96" x 1/4" mild steel capacity
- Front material guides
- Fast blade gap adjustment
- Shadow line for material placement
- 4-sided blades for long life
- 220V 3-phase



SH-70250-HD

- 120" x 1/4" mild steel capacity
- Front material guides
- Fast blade gap adjustment
- Shadow line for material placement
- 4-sided blades for long life
- 220V 3-phase

SPECIFICATIONS – SH-120250-HD		
Shear Length	120"	3048 mm
Max. Material Thickness		
Mild Steel	.250"	6.35 mm
Stainless Steel	.157"	4 mm
Minimum Thickness	18 ga.	
Strokes per Minute	15	
Back Gauge Length	25.6" / 650 mm (motorized)	
Blade Rake Angle	.5° – 1.5°	
Blade Clearance	Manual Hand Wheel	
Motor	15 hp	
Power Requirements	220V 3-Phase / 60 Hertz	
Shipping Dimensions (L x W x H)	154" x 64" x 77"	3920 x 1625 x 1955 mm
Shipping Weight	14,560 lbs.	6620 kgs.

Specifications subject to change without notice.



SH-120250-HD