

# Model 400 Series Specifications

POWER AIR SWEEPER

#### SWEEPING SYSTEM

Type Cleaning path: Minimum Sweeping Brush diameter Volume capacity (max) Disposable Bag Size Vacuum Impeller Diameter Vacuum Impeller Construction

Vacuum Impeller Housing

Vacuum Impeller Speed Debris Reduction Suction Head Vacuum Hose Diameter Whoosh Wander Hose: Length Diameter Brush Reach (Beyond Front of Unit)

# **PROPELLING SYSTEM**

Engine-standard (liquid cooled-Tier 4) Kub Fuel Capacity Fuel Consumption (estimate) Travel speed Model 414 Line Model 424HS Reverse Sweeping speed Stopping Distance (25%/11° Grade) Drive Tires (2), pneumatic, 6-ply - Tire Pressure Rear Wheels - Construction Model 414 Walk Behind (2) Model 414 w/RS option (2) Model 424 HS (2)

# DUST CONTROL SYSTEM

Dust Filtration System Stage 1 Stage 2 Dust Suppression System Spray Nozzles Side brush water spray dust control Water Control

# **OPERATOR ERGONOMICS**

Quiet Operation Easy to Use Whoosh Wander Hose Manual Brush Raise/Lowering (414) Large Oversized Zipper on Debris Bag Sight Lines to Sidebrushes No Tool Brush Change

# SAFETY SYSTEM

 Head and Tail Lights
 Warning light

 Rear View Mirrors (LH/RH)
 Automatic Braking if Handles Released

 Audible Warning System "Caution Sweeper Approaching"
 Floating Suction Head

Air Sweeper		
47-inch   1,170 mm		
18-inch   460 mm		
75 gal   284 L		
30 -55 Gal (110-200L) Standard Trash Bag		
16.6-inches   420 mm		
6 Blade Abrasion Resistant Steel		
with Hard Faced Edges		
Stainless Steel		
.25 inch (6mm) Replaceable Wear Plates		
up to 2,800 rpm		
Pulverizing Impeller		
Floating Aluminum w/Replaceable Skids		
8-inch   200 mm		
8-foot   2.6 m		
4-inch   100 mm		
17-inch   440 mm		

Kubota Z482-E diesel 14 hp (10.4 kW) 2.5 gal | 9.5 liter .25 gal/hr | 1 L/hr 0-5.5 mph | 0-8.8 km/h

> 0-10 mph | 0-16 km/h 0-3 mph | 0-4.8 km/h 0-5 mph | 0-8 km/h 2 ft | 610 mm 47 psi | 3.2 bar

Solid Rubber Caster Pneumatic Pneumatic

Two Stage Filtration Nylon Debris Screen Synthetic Dual Material Washable Filter Bag

> Each Brush & at Vacuum Inlet 14.5 gallon | 55 liter Variable by Operator

Ergonomic Control Handles Simple daily maintenance Power Brush Raise/Lower (424) Weather Proof Storage Compartment Fold and Stow Seat (RS option) Center Pivot Steering for Easy Maneuvering

# MACHINE DIMENSIONS

Width:	All Versions	46-inch   1,140 mm
Length:	Model 414 Walk Behind Model 414 RS Option Model 424 HS	99-inch   2,510 mm 121-inch   3,075 mm 142-inch   3,615 mm
Height:	Model 414 Walk Behind Model 414 RS Option Model 424 HS Model 424 HS (cab)	45-inch   1,120 mm 50-inch   1,270 mm 55-inch   1,400 mm 75-inch   1,905 mm
Weight:	Model 414 Walk Behind (ne Model 414 RS (net) Model 424 HS (net)	t) 926 lb   420 kg 1,015 lb   460 kg 1,150 lb   520 kg
Turning	Circle (Walk-Behind Mode):	99-inch   2510 mm

# **OPTIONAL EQUIPMENT**

Customized Coloring

75 Gal (284 L) Burlap Leafing Bag

Clean & Safe Attachment (hygienic removal of Dog Waste)

Snow Plow (not available on 424)

Recycling Center (424 Only)

All Weather Cab - No Tool Attachment (424 Only)

Fold and Stow Seat (RS Seat Option - 414 only)

# WARRANTY

Please refer to your local Tennant representative or Green Machine Dealer for information.



Model 414 RS Seat Option



Model 424 HS

Tennant Company | 701 N. Lilac Drive | P.O. Box 1452 | Minneapolis MN 55440-1452 | 800.553.8033 | www.tennantco.com | info@tennantco.com Specifications subject to change without notice. REV 01.01.09