



## SUPER RAKE 48<sup>volt</sup>

<b>MODEL</b>	<b>8440 Super Star 48<sup>volt</sup> Electric Power</b>
<b>POWER</b>	48 Volt electric motor, 5 HP Peak; 3.8HP continuous duty; 4 x 12 Volt deep cycle batteries Regenerative braking system to add power to batteries when brakes are applied. Low Speed control to maintain speed of 1 mph (1.6 kph) when operator is not present or machine is coasting downhill. Charging system with single plug to 110 volt or 220 volt charger (purchaser choice)
<b>CONFIGURATION</b>	3-wheel tricycle configuration, Rear motor placement.
<b>DRIVE</b>	Direct motor mounting to geared transaxle, 6:1 ratio
<b>SPEED</b>	0-12 mph (0-20 kph)
<b>BRAKING</b>	Drum braking on transaxle. Foot pedal actuated. Hand Brake Brakes Brake through dynamic braking.
<b>CONSTRUCTION</b>	Heavy gauge steel tubing, hydraulically formed, electrically welded.
<b>TIRES/WHEELS</b>	Purchasers choice of (3) 22-1100 x 8 knobbed sand tires, -or- (3) 22-1100 by 8 turf tires
<b>STEERING</b>	Manual front wheel steering, 15" (38 cm) diameter automotive type steering wheel with adjustable tilt
<b>CONTROLS</b>	Foot pedal accelerator, foot pedal brake Electric actuator for rear implement lift/lower Electric actuator for center mounted implements
<b>SEAT</b>	Deluxe seat, padded, vinyl covered, 1 piece molded, 1/2 back support
<b>SOUND LEVEL</b>	50 dB(A) under normal operating conditions
<b>DIMENSIONS (Inches/cm) (Length-Width-Height)</b>	56 in (142 cm)-74 in (187 cm)-46 in (116 cm); Wheelbase: 40 in (101 cm) Ground Clearance 9 in (23 cm) –under cultivator
<b>WEIGHT</b>	<b>925 lbs (420 kg)</b>
<b>SAFETY &amp; CONFORMANCE</b>	Complies with all applicable ANSI, OSHA standards Master electrical system disconnect switch with Emergency knob, electrical type fire extinguisher
<b>IMPLEMENTS</b>	Many efficient and effective implements for constructing and maintaining sand bunkers and other areas on the golf course.
<b>OPTIONS</b>	832-016      48-Volt Charger for 110 Volt - 60 cycle 832-316      48-Volt World Charger for all voltages and frequencies

		<b>SHIP WT.</b>
<b>Rear Mounted Implements</b>		
<b>7317</b>	Drag Mat Kit	40
<b>26-007</b>	Professional Infield Finisher	63
<b>26-008</b>	Flex Action Infield Finisher- Leveler	110
<b>43-002</b>	Flex Action Infield Finisher- Leveler with Brush	110
<b>43-043</b>	Brush (only) for Flex Action Finisher-Leveler	10
<b>Center Mounted Implements</b>		
<b>42-010</b>	Construction Leveling Blade	38
<b>42-178</b>	Infield Scarifier (with gauge wheels, vertical blades)	40
<b>42-179</b>	Infield Scarifier (with gauge wheels, chisel blades)	40
<b>42-210</b>	Grader Blade Kit (f/ 42-178 & 42-179)	10
<b>42-341</b>	Infield Scarifier (with spring tine teeth, gauge wheels)	40
<b>42-401</b>	Manual Lift for Center Implements	20
<b>Front Mounted Implements</b>		
<b>42-011</b>	40" (102 cm) Front Mounted Plow (aluminum blade)	65