AP500E Asphalt Paver



Smoothness Built-in

- Wheel undercarriage
 - Oscillating front wheels easily overcome obstacles with minimial tow-point movement
 - Large ground-contact area delivers good flotation and traction
- Advanced screed assist
 - Provides upward force on the screed, eliminates settling - Independent settings for standby and pave modes
- Material Delivery System
 - AS4252C screed with single main screed plate provides rigidity and stability
 - Independent control of each auger and each conveyor
 - automatic controls ensure precise delivery
 - Over-sized components run slower for reduced material segregation and parts wear

0	Ø	110	
Settin	gs:Disp	way:Lar	guage
0			
italan German		Press () to change the	
()			

Advisor Display

Ultimate Operator Comfort

- Total fumes management
 - Optimizes air-flow for improved operating conditions, engine cooling system, optional ventilation system
- Good visibility to truck driver, hopper, auger chamber, finished mat
- Dual Operating Stations
 - Easily change operating side with flip of switch
 - No bundles of cables and hoses to move from side to side - Redundancy in controls keep paver running
- Simple to use controls
 - Automotive-type steering wheels
 - Rugged switches with tactile feel
 - Cat[®] Advisor provides on-board diagnostics, calibrations, and parameter settings to match operator preferences



Mobility Between Jobs

- High travel speed of 16 km/hr
- 16 700 kg operating weight w/AS4252C, ideal size to transport with 7 or 10 ton roller

Versatility

- Wheel undercarriage
- Stability, traction, mobility, and ride quality
- AS4252C Screed
 - Up to 7 m paving width
 - 3200 kg weight
 - Single main screed plate
 - Cat Grade and Slope controls
 - Optimized operator access to tractor

Mobility on the Job

- Three propel/steering modes modify response for better control
 - Pave, travel and maneuver
 - Maneuver mode provides an industry best inside turning radius of 0.75 m
- Steering assist
 - Power is distributed to rear wheels according to steering angle of front wheels
 - Traction to pave through turns and push trucks around curves
- Front wheel assist and all-wheel drive options



AP500E Asphalt Paver Specifications

Operating Weights*		
Tractor	12 945 kg	28,539 lb
with AS4252C	16 145 kg	35,594 lb
Machine Dimensions (operating)	C C	
Tractor length with push roller	4.38 m	(14' 4")
Overall machine length w/screed		
AS4252C (walkway deployed)	5.75 m	(18' 10")
Tractor operating width (hopper lowered)	3.31 m	(10' 10")
Transport Dimensions		
Transport height (exhaust, canopy, seat lowered)	3.10 m	(10' 2")
Transport width with screed end gates (hopper raised)	2.75 m	(9' 0")
Transport width w/o screed end gates (hopper raised)	2.55 m	(8' 4")
Screed Paving Width		

AS4252C, maximum range	2.55 m - 7.0 m	8' 2" - 23'
Maximum paving depth	305 mm	12"

Optional Equipment

- Auger and Mainframe Extensions
- Auxiliary Power Panel
- Canopy (Folding)
- Decelerator Pedals
 Ecological Website
- Ecological Washdown System and Hose Reel
- Feeder Sensor (Mechanical or Sonic)
- Front Wheel Assist or All-Wheel Drive
- Fumes Extraction
- Grade and Slope Controls (Cat/Topcon)
- Leveling Devices
- Lights (Working or Roading)
- Oscillating Push Roller
- Power Folding Front Apron
- Power Mainframe Extensions
- Product Link
- Road Homologation
- Screed Extensions
- Tow-point Indicators (Upper)
- Truck Hitch
- Umbrella
- Up-time Kit
- Warning Beacon
- Wide Width Paving Packages

Optional equipment may vary per region, contact your local Cat Dealer for more information.

The Cat[®] Advantage - Single Source Provider

	Cat Dealer	Competitive Dealer	Comment
Convenient worldwide dealer locations	~		More than our 5 largest competitors combined
Engine service	~		Cat machines feature Cat engines
Machine service	~	~	
Service technician trained for paving equipment	~		Cat technicians trained on Cat machines
24/7/365 parts availability on most service parts	~		Long lead times for competitive OEM parts
New OEM parts	~		Competition offers inferior aftermarket parts
Reconditioned OEM parts	~		Rebuilt to OEM spec by Cat Reman
Available financing options	~		Available through Cat Financial
Application expertise	~		Personnel understand the paving business
Machine rental	~		Keeps your capital expense low
Products with high resale value	 ✓ 		Durable Cat machines built to last

QEXQ2127 (3/12)

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2012 Caterpillar All Rights Reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

