

SPECIFICATIONS
MODEL T-650B
POWER BOX® SELF PROPELLED ASPHALT PAVER

| | |
|----------------------------|---|
| Power Plant | Four Cylinder Engine, 30 H.P. (22.4 KW) Key Start |
| Empty Weight | 8055 Pounds (3648.9 Kg) |
| Fuel Capacity | 12 U.S. Gallons (45 liters) |
| Hydraulic Reservoir | 18 U.S. Gallons (66 liters) Dexron II. Pressure Tank 10psi. (.077 Bar) |
| Washdown Tank | 4 U.S. Gallons (15 liters) Diesel Fuel, Electrically Operated |
| Overall Width | 9 feet 10 inches (299.7 cm) |
| Overall Length | 8 feet (243.8 cm) |
| Overall Height | 5 feet 5 inches (165 cm) |
| Operative Speed | 0-130 FPM (39.6 mpm) |
| Paving Width | Basic—9 feet (274.3 cm). Variable 4½ feet (137.2 cm) to 12 feet (365.8 cm) |
| Paving Depth | 0-6 inches (0-15.2 cm) |
| Screed | Free Floating, Exhaust Heated, Mounted Vibrator, 2 Cylinder Lift |
| Crown or Invert | 2 inch (5.1 cm) Manual Adjustment |
| Material Flow Gates | Two independent hydraulically operated 4½ feet (137.2 cm) wide adjustable flow gates working hydraulically with two adjustable side gates |
| Augers | Separate Pump for each motor—automatic off |
| Tracks | Independent, Self Adjusting, Self Cleaning |
| Steering | Dual Mode—Lever or Wheel |
| Braking | Dynamic |
| Push Rollers | Sealed Ball Bearing |